

AEROSPACE

AMERICA

Bay City, Michigan 800-237-6414 / 989-684-2121

MANUFACTURER OF FILTRATION EQUIPMENT FOR INDOOR AIR QUALITY



9143 ECONO

aerospaceamerica.com

AIR FILTRATION

AEROCLEAN 2000 "Turbo Air" #9100

FEATURES: MADE IN THE U.S.A.

- Hour Meter (optional)
- Air Capacity 2300 C.F.M. High Speed
- Air Capacity 2000 C.F.M. Low Speed
 Motor: 1.0 H.P. (two speed switch)
- 33" Length x 26" Width x 26" Height
- Slide Down Door for E-Z accessibility
- Four (4) Casters for E-Z mobility
- Four (4) Handles
- 12" Exhaust
- Filters: 1st Stage 24" x 24" Pre-Filter

2nd Stage - 24" x 24" x 1" Ring Panel 3rd Stage - 24" x 24" x 11%" H.E.P.A. Filter



Made from aircraft grade aluminum for reduced weight (140 lbs.)

AEROCLEAN 2000 "Full Feature" #9103

FEATURES: MADE IN THE U.S.A.

- Audio & Visual Alarms
- Hour Meter (optional)
- Air Capacity 1950 C.F.M. High Speed
 Air Capacity 1300 C.F.M. Low Speed
 Motor: 1.0 H.P. (two speed switch)

- 33" Length x 26" Width x 26" Height
- Slide Down Door for E-Z accessibility
- Four (4) Casters for E-Z mobilityFour (4) Handles
- 12" Exhaust
- Filters: 1st Stage 24" x 24" Pre-Filter

2nd Stage - 24" x 24" x 1" Ring Panel 3rd Stage - 24" x 24" x 11%" H.E.P.A. Filter



Made from aircraft grade aluminum for reduced weight (125 lbs.)

AEROCLEAN 2000 "ECONO" #9143

FEATURES: MADE IN THE U.S.A.

- Air Capacity 1950 C.F.M. High Speed
- Air Capacity 1300 C.F.M. Low Speed
- Motor: 1.0 H.P. (two speed switch)
- 33" Length x 26" Width x 26" Height
- Slide Down Door for E-Z accessibility
- Four (4) Casters for E-Z mobility
- Four (4) Handles
- 12" Exhaust
- Filters: 1st Stage 24" x 24" Pre-Filter

2nd Stage - 24" x 24" x 1" Ring Panel

3rd Stage - 24" x 24" x 11%" H.E.P.A. Filter



Made from aircraft grade aluminum for reduced weight (120 lbs.)





900 Truman Parkway, Bay City, MI 48706 PH: 989-684-2121 or 1-800-237-6414

SPECIFICATIONS FOR AEROCLEAN 9143 2000 ECONO

MODEL #9143

MADE FROM AIRCRAFT ALUMINUM FOR REDUCED WEIGHT

AIR CAPACITY: 1950 C.F.M. HIGH SPEED

1300 C.F.M. LOW SPEED

(1.9 RUNNING STATIC PRESSURE)

POWER: 115 VOLTS AT 9.4 RUNNING AMPS

MOTOR: 1.0 H.P. TWO-SPEED THERMAL PROTECTED

BLOWER: 2000 A.M.C.A. RATED DIRECT DRIVE BLOWER

FILTERS: 1ST STAGE: 24 X 24 PRE FILTER

2ND STAGE: 24 X 24 RING PANEL 3RD STAGE; 24 X 24 HEPA FILTER

CASTERS: HEAVY DUTY: 2 SWIVEL, 2 RIGID

HANDLES: 4 PER UNIT

DIMENSIONS: 26" WIDTH

26" HEIGHT 33" LENGTH

INSTRUMENTATION: MINIHELIC PRESSURE GAUGE

PUSH BUTTON CIRCUIT BREAKER TWO SPEED ROCKER SWITCH

WEIGHT: 131 POUNDS